PRETREATmaker Basic Pro

TO SUPPORT VIRTUALLY ANY
SIZE GARMENT BUSINESS

Upgraded pretreatment features to keep your workflow moving

NEW FEATURES!

- Three tanks for different pretreatment formulas
- Larger front window for improved visibility
- Automatic nozzle cleaning feature every 15 seconds and added drip tray

ALSO WITH:

- Stepper motor for smooth, accurate spray patterns
- Fully enclosed spray chamber, side rails with splash guards, and drip tray
- Large side door and quick-release nozzle for easy daily cleaning
- Fast switching option to choose from three pretreatment liquids
- Large spray area (15.7" × 17.7")
- Durable zinc and powder-coated housing and compact size (27.5" × 20.5" × 22")



TO UPGRADE YOUR PRETREATMENT CAPABILITIES, CONTACT BROTHER DTG AT 866-750-2542 OR VISIT BrotherDTG.com.



SCHULZE





TECHNICAL SPECIFICATIONS

SPRAY AREA	15.7 × 17.7" (40 × 45 cm)
SPRAYING METHOD	Nozzle is moving over the table (inside)
TABLE LENGTH	24.4" (62 cm)
SPRAY DIRECTION	Uni / Bi-Directional
NOZZLES	1 Nozzle
NUMBER OF BOTTLES	Three Pretreat (2 Liter Bottles), One Water (2 Liter), One Waste (2 Liter)
MOTOR	Stepper Motor
PUMPS	One pump
DIMENSIONS	L 27.5" × W 20.5" × H 22.0" (L 70 × W 52 × H 56 cm)
DIMENSIONS (TRANSPORT)	L 31.5" × W 22.8" × H 28.7" (L 80 × W 58 × H 73 cm)
WEIGHT	84 lbs. (38 kg)
WEIGHT (TRANSPORT)	104 lbs. (47 kg)
CONNECTION	220/230 or 110/120 VAC (automatic switch)
CONSUMPTION	150 W
OPERATING PRESSURE (PRECOATING)	Max. 7 bar
INCLUDED IN DELIVERY	Replacement nozzle, replacement filter and ultrasound cleaner
ADDITIONAL CHARACTERISTICS	Zinc- and powder-coated housing

